

# See the **NEW JOHN DEERE** **110 Lawn and Garden Tractor**

*Try its exclusive Independent  
ground-speed control*



## *Outstanding Features:*

- 7 h.p. 4-cycle engine
- Ignition key (neutral gear) safety starter
- Fiber glass hood and fenders
- Brakes both rear wheels
- Turns outside a 28-inch-radius circle
- Adjustable rear-wheel tread . . . 27 or 33 inches

*Exclusive 3-way ground-speed control . . .*

*3 speeds forward, one reverse in 7 speed ranges . . . on-the-go  
speed change controlled by clutch pedal, speed-control lever, and throttle*







**38-INCH ROTARY MOWER** has three cutting blades, rear gauge wheels, and rollers to prevent scalping. Attaches in minutes. Safety feature: mower must be disengaged before tractor engine can be started.

### SPECIFICATIONS:

(Specifications and design subject to change without notice.)

**Engine:** 4 cycle, 7 h.p.

Kohler K 161 S

**Fuel Tank:** 1.9 U.S. gallons

**Starter:** Ignition key (neutral gear) safety starting

**Electrical:** 12-volt system

**Transaxle:** Three speeds forward and one reverse

**Variable Speed:** Lever-controlled, 7 ranges in each gear

**Gear Speeds:**

Forward 2-4-6 mph

Reverse 3½ mph

1st gear variable .9 to 2.5 mph

2nd gear variable 1.6 to 4.5 mph

3rd gear variable 2.4 to 6.6 mph

Reverse variable 1.2 to 3.4 mph

**Clutch:** Hard-backed V-belt type

**Brake:** Double-acting to both rear wheels



**36-INCH SNOW THROWER** cleans snow away in a hurry. Handy control swivels discharge spout a full 270°. Direct V-belt drive from engine powershaft. Snow thrower goes on or off in just a few minutes.

**Steering:** Variable ratio, enclosed gear

**Turns Outside:** 28-inch left-hand turning radius

**Parking Brake:** Finger-tip lock to foot brake

**Wheelbase:** 44 inches

**Wheel Tread**

Front: 28.8 inches

Rear: 27 or 33 inches

**Tires:** 4.00 x 8 front

6.00 x 12 rear (all-purpose tread)

**Seat Cushion:** Plastic-covered foam

**Hood and Fenders:** Fiber glass

### ACCESSORIES

Rear-Wheel Weights

Front-End Weights

Tire Chains (rear)

Clear Plastic Display and Rain Cover

Chrome Hub Caps

Integral Hitch

• 6 Months' Warranty • Easy Finance Terms Available

**42-INCH FRONT BLADE** angles 15° or 30° to right or left. Has a reversible hardened-steel cutting edge. Works from 2 inches below to 8 inches above the ground level. Trip springs prevent blade damage.



**FULL-LINE ALLIED ATTACHMENTS:** plow, disk, harrow, rake, planter, dump cart, and many other attachments are adapted for "one pin" integral hitch. Takes only a few minutes to switch from one tool to another.

